

Introduction

This guide is intended for developers who are integrating the AdView iOS SDK. After you have integrated the SDK, you must choose the relevant ad format and follow the steps for implementing that format.

Prerequisites

- iOS 8.0+


Step 1: Sign up and acquire AppId

Before integration, you need to sign up on **AdView Mobile Marketplace** first and acquire a specific AdView App id **SDK-KEY** for each app you would like to integrate with AdView SDK.

1. Sign up your publisher account at AdView Official Website:

<https://www.adview.com/web/overseas/register>

2. Sign in with your user name and password, AdView Publisher Dashboard opens
3. On the above menu bar, click **Apps**
4. On the left-up corner, click **+Add apps**



5. Fill in the app information step by step, please select the correct ad format, otherwise you might not get any ad fill. After filling all the necessary app information, please submit the app information for review. The review process generally takes one business day, please contact your account manager if any questions.

A screenshot of the 'Add App' form in the AdView Publisher Dashboard. The form is divided into three steps: 'Add App' (step 1), 'Select Platforms' (step 2), and 'Download SDK/Get links' (step 3). The 'Add App' section includes 'App information' and 'Ad configuration' fields. Under 'App information', there are radio buttons for 'Inventory Type' (App, Web, CTV), a text field for 'App name', radio buttons for 'OS' (iOS, Android, Other), and dropdown menus for 'Primary Category' and 'Secondary Category'. Under 'Ad configuration', there are dropdown menus for 'Banner refresh time' and 'Splash screen display time', and a toggle switch for 'Region optimization' which is currently turned 'ON'.

6. After the app has passed the review, the app **Status** will become **Passed** as below, please click **Configure** to config the ad network mediation configuration.

Type	OS	App name	SDK-KEY	Status	Creation date	Options
App	iOS	test	SDK20170718071104q00c8v9aeiis7py	Passed	2017-11-18	Edit Configure Delete

7. If you are using AdView's ad network mediation feature, please click **Add ad platform** to add the ad networks you would like to support. If you are already using other ad mediation solutions, please simply turn the Advertising platform **AdViewBID** on and set the capacity to 100%. You can also find the specific AdView app id **SDK-KEY** here, which you will need for the SDK integration.

Advertising platform	Scoring	Setting	On/off	Capacity	Priority	Operate
AdViewBID	4.86	Setting	<input checked="" type="checkbox"/>	100%		
GDT	2.98	not set	<input type="checkbox"/>	0%	+	Delete
Baidu	2.27	not set	<input type="checkbox"/>	0%	+	Delete
InMobi	1.72	not set	<input type="checkbox"/>	0%	+	Delete
AdDirect	1.28	Setting	<input type="checkbox"/>	0%	+	
AdExchange	1.33	Setting	<input type="checkbox"/>	0%	+	

8. If your app's ad format is Video or Native, you need to create **ad placement** for each ad place in your app. Please select **Ad Placement** on the above menu bar and click **+Ad Placement**, then add the necessary ad placement information accordingly.

Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date	Options
------	----	-----------	----------	---------	----	--------------	--------	---------------	---------

Step 2: Integration


Manual SDK Download

1. Download the latest Version SDK here:

2. Extract the zip file(Include: framework package, integration document, example)

Import the framework into your project

- If your xcode version is 11.0+ please put `AdViewSDK.xcframework`, otherwise please put `AdViewSDK.framework`.
- Add the dependency in YourProjectTarget's `Build Phases` - `Link Binary With Libraries`.
- Add `AdViewSDK.xcframework` or `AdViewSDK.framework` in `Build Phases` - `Embed Frameworks`.
- Set Embed type as Embed & Sign.



- if you want to use omsdk feature, also `OMSDK_Adview.framework` will be imported.

dependencies:

```
libc++.tbd  
libxml2.tbd
```

Update Your Project Settings

1. Declare the following permissions in your `Info.plist`:

App Transport Security Settings - Allow Arbitrary Loads - YES

2. Declare the following Flags in your `Build Settings`:

Build Settings - Other Linker Flags - `"-objc"`


Step 3: Configure Ad Units in Your App

Banner


Banner ads usually appear at the top or bottom of your app's screen. Adding one to your app takes just a few lines of code.

Create an APP in the Publisher UI for instructions. You will need that Ad Placement ID and SDK-KEY.

Usually when you add an app, you have the option of automatically ad banner or mrec ad placement.



Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date
mrec vid...	POSIDjpk31h7w81xn	video	test	SDK20151708050753ixgze1unq0v7zlv	iOS	Pending		2019-08-14
320x50	POSID7mevermixs0y	Banner	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14
320x480	POSIDycpnqrersov	Interstitial screen	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14
300x250	POSID6sv9wncud6sa	mrec	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14



Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date
mrec vid...	POSIDjpk31h7w81xn	video	test	SDK20151708050753ixgze1unq0v7zlv	iOS	Pending		2019-08-14
320x50	POSID7mevermixs0y	Banner	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14
320x480	POSIDycpnqrersov	Interstitial screen	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14
300x250	POSID6sv9wncud6sa	mrec	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending		2019-08-14

1. Init the Banner AdView

The AdView SDK provides a UIView subclass `AdViewview`, which handles requesting and loading ads. We provide the following methods for you to set up this subclass:

```
+ (AdViewview *)requestBannerSize:(AdViewBannerSize)size
                        bannerType:(AdViewBannerType)type
                        positionId:(NSString *)positionId
                        delegate:(id<AdViewviewDelegate>)delegate;

- (NSString *)appId;
```

```
self.banner = [AdViewview requestBannerSize:AdViewBannerSize_320x50
                        bannerType:AdViewBannerType_normal
                        positionId:@"POSID6uooxjk893j0"
                        delegate:self];

[self.view addSubview:self.banner];
```

Only MREC mode banner need `Position ID`.

```

self.MREC = [AdViewView requestBannerSize:AdViewBannerSize_300x250
                    bannerType:AdViewBannerType_video
                    positionId:@"POSID4zt29dh4zbp4"
                    delegate:self];

[self.view addSubview:self.MREC];

- (NSString *)appId {
    return @"SDK20191028101142e1ckebuvuy51czp";
}

```

return the `SDK-KEY` in protocol function `- (NSString *)appId;`

Choose the ad size you need, we recommend 728x90 for tablet traffic and 320x50 for mobile traffic. The default size of MREC is 300x250, more define as following, all definitions are in `AdViewDefinesPublic.h` note the corresponding value. In addition, MREC currently supports the display of video advertisements, which will be described in detail below.

```

typedef NS_ENUM(NSInteger, AdViewBannerSize) {
    AdViewBannerSize_320x50,
    AdViewBannerSize_480x44,
    AdViewBannerSize_300x250,    //MREC
    AdViewBannerSize_480x60,
    AdViewBannerSize_728x90,
};

```

And the Banner type:

```

typedef NS_ENUM(NSInteger, AdViewBannerType) {
    AdViewBannerType_normal,    //Html5、Image
    AdViewBannerType_video      //Video
};

```

2. Should not change the Ad's bounds, because it may cause some error. But you can change the origin in the visible area.
3. Using the Delegate *AdViewViewDelegate.h*

which includes a variety of optional callbacks you can use to be notified of events. For example, when an ad has successfully loaded, or when the ad is about to present or dismiss a modal view.

`AdViewDelegate` is a interface includes the following notifications:

```

@protocol AdViewViewDelegate <AdViewGDPRProtocol>
@required
- (NSString *)appId;
- (UIViewController *)viewControllerForShowModal;
@optional
- (void)didReceivedAd:(AdViewView *)adView;
- (void)didFailToReceiveAd:(AdViewView *)adView Error:(NSError*)error;
- (void)adViewWillPresentScreen:(AdViewView *)adView;
- (void)adViewDidDismissScreen:(AdViewView *)adView;
- (void)adViewDidFinishShow:(AdViewView *)adView;
- (int)autoRefreshInterval;
- (BOOL)logMode;
...
@end

```

4. Refresh time set

You can use `-(int)autoRefreshInterval` to return the automatic refresh time of banner. The minimum refresh time allowed by AdView is 30s, so when you set the refresh time between 1 and 30 seconds, the default refresh time is 30 seconds.

```
- (int)autoRefreshInterval {  
    return 30;  
}
```


If you set the refresh time to 0, which means the banner will not automatically refresh. The ads will **expire in 10 minutes**. So please notice the ad's life cycle, release old ad then reinitialize the new banner.

Interstitial

Interstitial ads provide full-screen experiences, commonly incorporating rich media to offer a higher level of interactivity compared to banner ads. Interstitials are typically shown during natural transitions in your app; for example, after completing a game level, or while waiting for a new view to load.

Create an APP in the Publisher UI for instructions. You will need that SDK-KEY.

Usually when you add an app, you have the option of automatically interstitial ad placement.



Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date
mrec vid...	POSIDjpk31h7w81xn	video	test	SDK20151708050753ixgze1unq0v7zlv	iOS	Pending		2019-08-14
320x50	POSID7mevermixs0y	Banner	test	SDK20191014100856oeq4gul9ditxxy	Android	Pending		2019-08-14
320x480	POSIDcycpnqrersov	Interstitial screen	test	SDK20191014100856oeq4gul9ditxxy	Android	Pending		2019-08-14
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK20191014100856oeq4gul9ditxxy	Android	Pending		2019-08-14
300x250	POSID6sv9wncud6sa	mrec	test	SDK20191014100856oeq4gul9ditxxy	Android	Pending		2019-08-14

1. Create an Interstitial Ad

Income the `delegate`、`SDK-KEY` and `viewControllerForShowModal` complete interstitial initialization:

```
+ (AdViewView *)requestAdInterstitialWithPositionId:(NSString *)positionId  
    delegate:(id<AdViewViewDelegate>)delegate;  
- (NSString *)appId;
```

```

self.interstitial = [AdViewView
requestAdInterstitialWithPositionId:@"POSIDajpz3chwo1q2"
delegate:self];

- (NSString *)appId {
    return @"SDK20191028101142e1ckeubuvuy5lczp";
}

- (UIViewController *)viewControllerForShowModal {
    return viewController;
}

```

2. Display an Interstitial Ad

When the advertisement is ready, you will receive the following callbacks:

```
- (void)didReceivedAd:(AdViewView *)adview
```

regularly, in *didReceivedAd*, it means ad is ready and can be shown as you need, you can call the show method, then ad will pop up to screen:

```

- (void)didReceivedAd:(AdViewView *)adview {
    [adview showInterstitialWithRootViewController:[UIApplication
sharedApplication].keywindow.rootViewController];
}

```

3. Using the Delegate

`AdViewViewDelegate.h` provides a listener interface, which includes a variety of optional callbacks you can use to be notified of events; for example, when an ad has successfully loaded, or when the ad is about to present or dismiss a modal view. The same as Banner.

Spread

Spread is usually an advertisement displayed at the start of app and usually has higher visibility than banner and interstitial.

Create an APP in the Publisher UI for instructions. You will need SDK-KEY.

ADVIEW									
Dashboard Apps Ad Placements Campaigns Reports Finance									
+Ad Placement Integration way		Ad Format		Status		Under review			
ID:		Name:		SDK-KEY:		Search			
Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date	
mrec vid...	POSIDjpk31h7w81xn	video	test	SDK20151708050753ixgze1unq0v7zlv	iOS	Pending	<input checked="" type="checkbox"/>	2019-08-14	Ed
320x50	POSID7mevermixs0y	Banner	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Ed
320x480	POSIDcycpnqrersov	Interstitial screen	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Ed
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Ed
300x250	POSID6sv9wncud6sa	mrec	test	SDK20191014100856oeq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Ed

1. Create an spread Ad

Income the following parameters and complete Spread initialization:

```
+ (AdView * )requestSpreadActivityWithPositionId:(NSString *)positionId
                                delegate:
(id<AdViewDelegate>)delegate;
- (NSString *)appId;
- (UIViewController *)viewControllerForShowModal;
```

You should write these code in the `AppDelegate.m`

```
- (BOOL)application:(UIApplication *)application didFinishLaunchingWithOptions:
(NSDictionary *)launchOptions {
    if (@available(iOS 13.0, *)) {

    } else {
        self.window = [[UIWindow alloc] initWithFrame:[UIScreen
mainScreen].bounds];
        [self.window setBackgroundColor:[UIColor whiteColor]];

        ViewController * vc = [[ViewController alloc] init];
        UINavigationController * navc = [[UINavigationController alloc]
initWithRootViewController:vc];
        [self.window setRootViewController:navc];
        [self.window makeKeyAndVisible];
    }
    [AdView requestSpreadActivityWithDelegate:self];
    return YES;
}
```

2. Display spread Ad

Usually spread will show automatically.

3. Using the Delegate

also, `AdViewDelegate.h` provides a listener interface, which includes a variety of optional callbacks you can use to be notified of events.

```
- (NSString *)appId;
- (UIViewController *)viewControllerForShowModal;
- (NSString *)logoImgName;
```

Native

Native ads make it easy for you to monetize your app in a way that's consistent with its existing design. The AdView SDK gives you access to an ad's individual assets so you can design the ad layout to be consistent with the look and feel of your app.

Init the Native Ad You will need that Ad Position ID and SDK-KEY.

You need to choose the right creative and image size when creating native ad placement.

Create Ad Placement

App Name: * test

Name: * native example: app_name+position+style ✔ passed

Ad Format: * ☒ Banner ☐ mrec ☐ Interstitial screen ☐ Splash Screen ☒ Native/Information ☐ video ☐ interactive effectiveness

Elements: ☒ Title ☒ Description ☒ Icon

The ad is matched based on the proximity of aspect ratio of your selected size, rather than a strict match

Dimension: * ☐ No Image

☐ One Image ☐ style1 (Size 1280x720) *recommended ☐ style2 (Size 1200x627)

Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date	
native	POSIDjqyjhkw8a2n8	Native/Information	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Edit
mrec vid...	POSIDjpk31h7w81xn	video	test	SDK20151708050753ixgze1unq0v7zlv	iOS	Pending	<input checked="" type="checkbox"/>	2019-08-14	Edit
320x50	POSID7mevermlxs0y	Banner	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Edit
320x480	POSIDcycpnqrersov	Interstitial screen	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Edit
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Edit
300x250	POSID6sv9wncud6sa	mrec	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<input checked="" type="checkbox"/>	2019-08-14	Edit

1. Create an AdView Native Ad:

```
- (instancetype)initWithAppKey:(NSString *)appkey positionID:(NSString *)positionID;
```

```
self.native = [[AdviewNativeAd alloc] initWithAppKey:ADVIEW_APPID
positionID:ADVIEW_NATIVE_POSITION_ID];
self.native.delegate = self;
self.native.controller = self;
```

2. Call `-(void)loadNativeAdWithCount:` to request an ad from the server and download associated images asynchronously.

```
[self.native loadNativeAdWithCount:1];
```

3. Display native Ad, after `-(void)adviewNativeAdSuccessToLoadAd:NativeData:` callback is called when native ad is downloaded from server.
Upon failure `-(void)adviewNativeAdFailToLoadAd:WithError:` callback is called with a corresponding error code message.

```

- (void)adViewNativeAdSuccessToLoadAd:(AdViewNativeAd *)adViewNativeAd
NativeData:(NSArray <AdViewNativeData *>*)nativeDataArray {
    //this is contentView, see demo
    self.nativeAdView = [[UIView alloc] init];

    //consuct the custom ad view

    //must use this function to send display
    [self.native showNativeAdWithData:nativeDataArray.firstObject
        friendlyObstructionArray:friendlyObstructionArray
        onView:self.nativeAdView];
}

```

according to **AdViewNativeData.adProperties** is a list contains items as following:

Normal native mode:

Figure native4.1

Name	Value Type	Description
adIcon	String	icon url for adview icon
adLogo	String	logo url for adview logo
desc	String	description
title	String	ad title string
imageList	Array	large images for ad resource
iconUrlString	String	icon for ad resource
pimage	String	opt-out icon
pclick	String	opt-out click url
ompara、omurl、omvendor	String	OMSDK

5. Using the Delegate

```

@protocol AdViewNativeAdDelegate <AdViewGDPRProcoto1>
- (void)adViewNativeAdSuccessToLoadAd:(AdViewNativeAd *)adViewNativeAd
NativeData:(NSArray <AdViewNativeData *>*)nativeDataArray;
- (void)adViewNativeAdFailToLoadAd:(AdViewNativeAd *)adViewNativeAd withError:
(NSError *)error;
- (void)adViewNativeAdWillShowPresent;
- (void)adViewNativeAdClosed;
- (void)adViewNativeAdResignActive;
@end

```

Opt-out

In line with new industry self-regulatory guidance provided by the DAA, AdView now requires all native ads to display the privacy information icon and click region. The icon must be at least 20x20px and can be placed in any one of the four corners of the ad.

You can use your own icon and privacy information page, or use the corresponding icons and privacy information pages provided by AdView, You can get them with **pimage** and **pclick**, see Figure native4.1.

demo codes for got privacy image :

```
NSString *optOutIconURL = data.adProperties[@"pimage"];
UIImageView *optOutIcon = [[UIImageView alloc] initWithImage:[UIImage
imageWithData:[NSData dataWithContentsOfURL:[NSURL
URLWithString:optOutIconURL]]]];
optOutIcon.userInteractionEnabled = YES;
UITapGestureRecognizer *optOutIconTap = [[UITapGestureRecognizer alloc]
initWithTarget:self action:@selector(optOutIconClick:)];
[optOutIcon addGestureRecognizer:optOutIconTap];
```

demo codes for privacy click URL, you can got click url with `NSString *optOutClickURL = data.adProperties[@"pclick"];` and show it by yourself.

```
//display privacy information
- (void)optOutIconClick:(id)sender {
    [[UIApplication sharedApplication] openURL:[NSURL
URLWithString:optOutClickURL]];
}
```

Video

Video Ads are shown in fullscreen mode and can be placed before, in-between, or after the app content.

Rewarded & Interstitial video

Create an APP in the Publisher UI for instructions. You will need that Ad Position ID and SDK-KEY.

ADVIEW™

Dashboard Apps Ad Placements Campaigns Reports Finance

Create Ad Placement

App Name: * test

Name: * rewarded video example: app_name+position+style passed

Ad Format: * ☐ Banner ☐ mrec ☐ Interstitial screen ☐ Splash Screen ☐ Native/Information ☒ video ☐ interactive effectiveness

Video Type: ☒ Incentive video ☐ Patch Video ☐ In-banner video ☐ Interstitial video

Video Format: ☒ MP4 ☐ FLV ☐ SWF

Video Size: 480x320

Maximum ad duration: ☒ Unlimited ☐ 15s ☐ 30s ☐ 45s ☐ 60s

skip: ☐ OFF

Save Cancel

+Ad Placement

Integration way

Ad Format

Status

Under review

ID:

Name:

SDK-KEY:

Search

Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date	
rewarded...	POSIDg0xokb25eeu0	video	test	SDK20191014100856oeq4gul9dtltxsy	Android	Pending		2019-08-14	Edi
native	POSIDjqyjhkw8a2n8	Native/information	test	SDK20191014100856oeq4gul9dtltxsy	Android	Pending		2019-08-14	Edi
mrec vid...	POSIDjp31h7w81xn	video	test	SDK20151708050753ixgze1unq0v7zlv	iOS	Pending		2019-08-14	Edi
320x50	POSID7mevermlxs0y	Banner	test	SDK20191014100856oeq4gul9dtltxsy	Android	Pending		2019-08-14	Edi
320x480	POSIDcypnqrsrov	Interstitial screen	test	SDK20191014100856oeq4gul9dtltxsy	Android	Pending		2019-08-14	Edi
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK20191014100856oeq4gul9dtltxsy	Android	Pending		2019-08-14	Edi
300x250	POSID6sv9wncud6sa	mrec	test	SDK20191014100856oeq4gul9dtltxsy	Android	Pending		2019-08-14	Edi

1. Create an Rewarded video Ad:

Income the following parameters and complete initialization:

```
self.video = [AdViewVideo playVideoWithAppId:ADVIEW_APPID
                        positionId:ADVIEW_VIDEO_POSITION_ID
                        videoType:AdViewVideoTypeInstl
                        delegate:self];
[self.video setInterfaceOrientations:[UIApplication
sharedApplication].statusBarOrientation];
[self.video getVideoAD];
```

callback **AdViewVideoDelegate** is call capture events from video SDK process.

```
@protocol AdViewVideoDelegate <AdViewGDPRProcoto1>
- (void)adviewVideoIsReadyToPlay:(AdViewVideo *)video;
- (void)adviewVideoPlayStarted;
- (void)adviewVideoPlayEnded;
- (void)adviewVideoClosed;
- (void)adviewVideoDidReceiveAd:(NSString *)vastString;
- (void)adviewVideoFailReceiveDataWithError:(NSError*)error;
```

AdView provides a response function `- (void)adviewVideoDidReceiveAd:` to let you know if the advertisement was successfully requested:

This function is called when the ad request is successful:

```
- (void)adviewVideoDidReceiveAd:(NSString *)vastString {
    NSLog(@"%@",vastString);
}
```

This function is called when an ad request fails:

```
- (void)adviewVideoFailReceiveDataWithError:(NSError *)error {
    NSLog(@"%@",error);
}
```

3. Called when the video ad is ready, after which video shows can be made:

```
- (void)adviewVideoIsReadyToPlay:(AdviewVideo *)video {  
    [video showVideoWithController:self];  
}
```

4. You can also monitor the following play status to determine rewards for users:

Called when video ads start playing

```
- (void)adviewVideoPlayStarted;
```

Called when video ads have ended

```
- (void)adviewVideoPlayEnded;
```

Called when the video ad is closed:

```
- (void)adviewVideoClosed;
```

Called when the video ad is playing incorrectly:

```
- (void)adviewVideoFailReceiveDataWithError:(NSError*)error;
```

PreMovie

PreMovie can provide video source (means VAST xml content) to app, and SDK will not show it. though app can parse vast itself and play it as it wish.

Create an APP in the Publisher UI for instructions. You will need that Ad Position ID and SDK-KEY.

The screenshot shows the 'Create Ad Placement' form in the ADVIEW Publisher UI. The form includes the following fields and options:

- App Name:** A dropdown menu with 'test' selected.
- Name:** A text input field with 'patch video' entered. A green checkmark and the text 'passed' are next to it.
- Ad Format:** Radio buttons for Banner, mrec, Interstitial screen, Splash Screen, Native/Information, **video** (highlighted with a red box), and interactive effectiveness.
- Video Type:** Radio buttons for Incentive video, **Patch Video** (highlighted with a red box), In-banner video, and Interstitial video.
- Patch Video:** Radio buttons for Pre-Roll, Mid-Roll, and Post-Roll.
- Video Format:** Checkboxes for MP4 (checked), FLV, and SWF.
- Video Size:** A dropdown menu with '640x360' selected.
- Maximum ad duration:** Radio buttons for Unlimited, 15s, 30s, 45s, and 60s.
- skip:** A toggle switch set to 'OFF'.

At the bottom of the form are 'Save' and 'Cancel' buttons.

ADVIEW™

Dashboard

Apps

Ad Placements

Campaigns

Reports

Finance

+Ad Placement

Integration way

Ad Format

Status

Under review

ID:

Name:

SDK-KEY:

Search

Name	ID	Ad Format	APP Name	SDK-KEY	OS	Under review	Status	Creation Date
patch vi...	POSID1yie9lu0b66	video	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
Intersti...	POSIDco629pajefni	video	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
rewarded...	POSIDg0xokb25eeu0	video	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
native	POSIDjqyjhkw8a2n8	Native/Information	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
mrec vid...	POSIDjpk31h7w81xn	video	test	SDK20151708050753ixge1unq0v7zlv	iOS	Pending	<div></div>	2019-08-14
320x50	POSID7mevermxs0y	Banner	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
320x480	POSIDcycpnqrersov	Interstitial screen	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
640x960	POSIDyk6re2drqpqn	Splash Screen	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14
300x250	POSID6sv9wncud6sa	mrec	test	SDK201910141008560eq4gul9ditlxsy	Android	Pending	<div></div>	2019-08-14

1. Create an paste video ad:

```
self.video = [Adviewvideo playvideowithAppId:ADVIEW_APPID
                positionId:ADVIEW_VIDEO_POSITION_ID
                videoType:AdviewvideoTypePreMovie
                delegate:self];
```

2. Response for video ad received:

with paste video mode, after ad video is received, the video contents will be pass through to app with callback `onReceivedVideo()`, in parameter string:

```
- (void)adviewvideoDidReceiveAd:(NSString *)vastString {
    NSLog(@"%@",vastString);
}
```

3. Play & other process:

same as rewarded video.

GDPR

As a publisher, you should integrate a Consent Management Platform (CMP) and request for vendor and purpose consents as outlined in IAB Europe's Mobile In-App CMP API v1.0: Transparency & Consent Framework. You can find a reference implementation of a web-based CMP and the corresponding native wrappers here in the IAB's GDPR Transparency and Consent Framework.

if you already got `IABConsent_ConsentString`, you just need pass through to SDK construction method as the last parameter. See `AdviewviewDelegate.h` - `AdviewGDPRProcoto1` :

```
@protocol AdViewGDPRProtocol <NSObject>
- (BOOL)CMPPresent;
- (BOOL)subjectToGDPR;
- (NSString *)userConsentString;
- (NSString *)parsedPurposeConsents;
- (NSString *)parsedVendorConsents;
@end
```

if **String gdpr** is empty, it means not support GDPR.

CCPA

The California Consumer Privacy Act (CCPA) was created to provide California consumers with greater transparency and control over their personal information. In many ways, the CCPA is a first of its kind regulation in the United States that seeks to create broad privacy and data protection rules that apply to all industries doing business in the jurisdiction of California, rather than focusing on a single sector or specific data collection and use practices.

For Publishers with California-Based Users

As a publisher, you need to make sure to request consent from California-based users (to give or refuse consent / to opt-out or opt-in) about private data transfer. This answer should be saved in `NSUserDefaults` with key `IABUSPrivacy_String` in the US Privacy String format (CCPA Opt-Out Storage Format).

Sample of US Privacy String Saving in NSUserDefaults

```
- (void)saveCCPAUSPrivacyString:(NSString *)usString {
    if (usString.length > 0) {
        [NSUserDefaults standardUserDefaults setObject:usString
                                                forKey:@"IABUSPrivacy_String"];
    }
}
```

AdView SDK reads that value by key "IABUSPrivacy_String" if it exists and uses it as an optional parameter for all ad requests.